

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED / ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371		ATTORNEY'S DOCKET NUMBER P67399US0
		US APPLICATION NO. (If known, see 37 CFR 1.51) 09/926745
INTERNATIONAL APPLICATION NO. PCT/NZ00/00093	INTERNATIONAL FILING DATE 9 June 2000	PRIORITY DATE CLAIMED 11 June 1999
TITLE OF INVENTION DEVICE FOR DELIVERY OF A LIQUID VEHICLE		
APPLICANT(S) FOR DO/EO/US Craig Robert BUNT, Michael John RATHBONE and Shane BURGGRAAF		

Applicant herein submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information.

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for Internatl. Preliminary Examination was made by the 19th month from earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US)
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the Internatl. Preliminary Examination report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A **FIRST** preliminary amendment.
☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:
 - International Search Report
 - PCT/IB/306 Form
 - First Page of Publication
 - International Preliminary Examination Report - with no annexes

US APPLICATION NO. (if known, see 37 CFR 1.5) <div style="font-size: 1.5em; font-weight: bold;">09/926745</div>		INTERNATIONAL APPLICATION NO. <div style="font-weight: bold;">PCT/NZ00/00093</div>		ATTORNEY'S DOCKET NUMBER <div style="font-weight: bold;">P67399US0</div>	
--	--	---	--	---	--

17. <input checked="" type="checkbox"/> The following fees are submitted: <div style="margin-left: 20px;"> Basic National Fee (37 CFR 1.492(a)(1)-(5)): Internatl. prelim. examination fee paid to USPTO (37 CFR 1.492 (a) (1)) .. \$710.00 No international preliminary examination fee paid to USPTO (37 CFR 1.492 (a) (2)) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) .. \$740.00 Neither international preliminary examination fee (37 CFR 1.492 (a) (3)) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO) \$1040.00 International preliminary examination fee paid to USPTO (37 CFR 1.492 (a) (4)) and all claims satisfied provisions of PCT Article 33(2)-(4) \$100.00 Search Report prepared by the EPO or JPO (37 CFR 1.492 (a) (5)) \$890.00 <div style="text-align: right; margin-right: 50px;">ENTER APPROPRIATE BASIC FEE AMOUNT =</div> </div>				CALCULATIONS	PTO USE ONLY
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$ 130.00	
Claims	Number Filed	Number Extra	Rate		
Total Claims	30 - 20 =	-10-	x \$18.00	\$ 180.00	
Independent Claims	3 - 3 =	-0-	x \$84.00	\$	
Multiple Dependent Claim(s) (if applicable)			+ \$280.00	\$	
TOTAL OF ABOVE CALCULATIONS =				\$ 1350.00	
Reduction by 1/2 for filing by small entity , if applicable. Verified Small Entity statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28).				\$	
SUBTOTAL =				\$ 1350.00	
Processing fee of \$130 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f))				\$	
TOTAL NATIONAL FEE =				\$ 1350.00	
Fee of \$40.00 for recording the enclosed assignment (37 CFR 1.21(h)). Assignment must be accompanied by appropriate cover sheet (37 CFR 3.28, 3.31).				\$	
TOTAL FEES ENCLOSED =				\$ 1350.00	
				Amt. to be refunded:	\$
				Amt. charged:	\$


a. ☒ A check in the amount of \$ 1350.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. 06-1358 in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge my account any additional fees set forth in §1.492 during the pendency of this application, or credit any overpayment to Deposit Account No. 06-1358. A duplicate copy of this sheet is enclosed.

SEND ALL CORRESPONDENCE TO:

JACOBSON HOLMAN PLLC
 400 7th Street, N.W., Suite 600
 Washington, DC 20004
 202-638-6666
CUSTOMER NUMBER: 00136

By 
 John C. Holman
 Reg. No. 22,769

JPH&S 3/95

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Craig Robert BUNT et al.

Serial No.: New

Filing Date: December 11, 2001

For: DEVICE FOR DELIVERY OF A LIQUID VEHICLE

PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, D.C. 20231

Sir:

Prior to initial examination, please amend the above-identified application as follows:

IN THE SPECIFICATION

On page 1, immediately following the title, please insert the following sentence: --This is a nationalization of PCT/NZ00/00093 filed June 9, 2000 and published in English.--

IN THE CLAIMS

Please amend claims 6, 7, 10, 11, 14, 15, 17-19, 21-23, 26, 27, 29 and 30 as follows:

6. (amended) A device of claim 1 wherein said electrical circuit provides a continuous rate of gas production by the action of a continuous current to the electrolysis cell or gas emitting battery.

7. (amended) A device of claim 1 wherein said electrical circuit

09/926745

provides a discontinuous rate of gas production by the action of a discontinuous current, as provided by a microprocessor, to the electrolysis cell or gas emitting battery.

10. (amended) A device as claimed in claim 1 wherein the battery powered electrical circuit is one having a known or calibrated profile of gas generation that will lead to a related profile of liquid release from said outlet.

11. (amended) A device as claimed in claim 1 which is an intra vaginal device.

14. (amended) A device as claimed in claim 1 wherein said liquid includes progesterone in an appropriate liquid carrier.

15. (amended) A device as claimed in claim 1 which is an intra ruminal device.

17. (amended) A device as claimed in claim 1 wherein said liquid includes at least one or more of water, ethanol and benzyl alcohol.

18. (amended) A device as claimed in claim 1 wherein said battery powered electrical circuit includes a switch capable of being actuated to immediately or after a delay commence the generation of a gas or gases.

19. (amended) A device as claimed in claim 1 wherein said outlet is provided with a closure capable of being removed, ruptured or dissolved in body fluids.

21. (amended) A device as claimed in claim 1 wherein said liquid is of a volume of from 5 to 100 mL and said piston is movable within said housing to express substantially all of such liquid from the housing.

22. (amended) A device of claim 1 insertable, retainable and removal from the vaginal tract of a target species mammal, there being a conduit or passageway disposed to allow pressure equalisation outside of the device at the innermost and outmost extent of the device in the vaginal tract.

23. (amended) A device as claimed in claim 1 substantially as hereinbefore described with reference to the accompanying drawings.

26. (amended) A method of providing an active release of a liquid within a body cavity of a target species mammal which comprises or includes locating in such a body cavity a device as claimed in claim 1 with said battery powered electrical circuit energised or committed to be energised.

27. (amended) A method of delivering an active amount of a progesterone into the vaginal tract of a target species mammal which comprises or includes locating a device as claimed in claim 1 in such tract after initiation of the device, and allowing the device to actively express the liquid from said housing under the effect, via said piston, of the gas or gases generated by the energised battery powered electrical circuit.

29. (amended) A method of providing delayed release of a liquid vehicle into a body cavity of a mammal or into a liquid environment

which comprises or includes the operative use of a device of claim 1.

30. (amended) A method as claimed in claim 26 when performed substantially as hereinbefore described with or without reference to any one or more of the accompanying drawings.

REMARKS

The foregoing Preliminary Amendment is requested in order to delete the multiple dependent claims and avoid paying the multiple dependent claims fee.


Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page is captioned "VERSION WITH MARKINGS TO SHOW CHANGES MADE."

Early action on the merits is respectfully requested.

Respectfully submitted,

JACOBSON HOLMAN PLLC

By


John C. Holman
Reg. No. 22,769

400 Seventh Street, N.W.
Washington, D.C. 20004-2201
(202) 638-6666

Atty. Docket: P67399US0
Date: December 11, 2001
JCH/cmf

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE CLAIMS

6. (amended) A device of claim 1 [any one of the preceding claims] wherein said electrical circuit provides a continuous rate of gas production by the action of a continuous current to the electrolysis cell or gas emitting battery.

7. (amended) A device of claim 1 [any one of claims 1 to 5] wherein said electrical circuit provides a discontinuous rate of gas production by the action of a discontinuous current, as provided by a microprocessor, to the electrolysis cell or gas emitting battery.

10. (amended) A device as claimed in claim 1 [any one of the preceding claims] wherein the battery powered electrical circuit is one having a known or calibrated profile of gas generation that will lead to a related profile of liquid release from said outlet.

11. (amended) A device as claimed in claim 1 [any one of the preceding claims] which is an intra vaginal device.

14. (amended) A device as claimed in claim 1 [any one of the preceding claims] wherein said liquid includes progesterone in an appropriate liquid carrier.

15. (amended) A device as claimed in claim 1 [any one of claims 1 to 10] which is an intra ruminal device.

17. (amended) A device as claimed in claim 1 [any one of the preceding claims] wherein said liquid includes at least one or more

of water, ethanol and benzyl alcohol.

18. (amended) A device as claimed in claim 1 [any one of the preceding claims] wherein said battery powered electrical circuit includes a switch capable of being actuated to immediately or after a delay commence the generation of a gas or gases.

19. (amended) A device as claimed in claim 1 [any one of the preceding claims] wherein said outlet is provided with a closure capable of being removed, ruptured or dissolved in body fluids.

21. (amended) A device as claimed in claim 1 [any one of the preceding claims] wherein said liquid is of a volume of from 5 to 100 mL and said piston is movable within said housing to express substantially all of such liquid from the housing.

22. (amended) A device of claim 1 [any one of the preceding claims] insertable, retainable and removal from the vaginal tract of a target species mammal, there being a conduit or passageway disposed to allow pressure equalisation outside of the device at the innermost and outmost extent of the device in the vaginal tract.

23. (amended) A device as claimed in claim 1 [any one of the preceding claims] substantially as hereinbefore described with reference to the accompanying drawings.

26. (amended) A method of providing an active release of a liquid within a body cavity of a target species mammal which comprises or includes locating in such a body cavity a device as claimed in claim 1 [any one of the preceding claims] with said battery powered electrical circuit energised or committed to be energised.

27. (amended) A method of delivering an active amount of a progesterone into the vaginal tract of a target species mammal which comprises or includes locating a device as claimed in claim 1 [any one of claims 1 to 25] in such tract after initiation of the device, and allowing the device to actively express the liquid from said housing under the effect, via said piston, of the gas or gases generated by the energised battery powered electrical circuit.

29. (amended) A method of providing delayed release of a liquid vehicle into a body cavity of a mammal or into a liquid environment which comprises or includes the operative use of a device of claim 1 [any one of claims 1 to 25].

30. (amended) A method as claimed in claim 26 [any one of claims 26 to 29] when performed substantially as hereinbefore described with or without reference to any one or more of the accompanying drawings.

DEVICE FOR DELIVERY OF A LIQUID VEHICLE**THE CURRENT INVENTION**

The present invention relates to improvements in the delivery of an active agent
5 into an environment (whether *in vivo* or *in vitro*) and particularly, although not solely,
to devices having application in the delivery of one or more active ingredients into a
mammal (eg; intra ruminally or intra vaginally) or into an aqueous environment, e.g. an
aquarium.

10 SUMMARY OF THE INVENTION

In our PCT/NZ98/00011 we disclose in some detail the background to the
passive and active release of active ingredient(s) into the body cavity of mammals
including the vaginal tract and the rumen. PCT/NZ96/00024 (WO 96/29025) discloses
a microprocessor controlled active release device for intra vaginal insertion with its
15 retention being dependent on variable geometries possible using deployment members
of a kind as disclosed in NZ Patent Specifications 193976 and 200564.

A problem discussed in such specification is the release profile of a substance
delivery device whether for a body cavity or otherwise (for example, a liquid body such
as an aquarium) arising from a passive leakage of material which can affect the overall
20 release profile.

We have investigated different known procedures of active release and have
considered new procedures insofar as the means of expression of a liquid vehicle from
a reservoir of reducible volume is concerned. It is to such substance delivery devices
and their use that the present invention is directed.

25 In a first aspect the present invention consists in a (preferably body cavity)
liquid delivery device comprising or including
a housing defining a barrel with an outlet,
a piston disposed in said barrel and moveable to reduce the available volume for
liquid between said piston and said outlet,
30 a liquid within said barrel between said outlet and said piston, and
a battery powered electrical circuit disposed in said housing capable of being

energised to generate gas or gases confined within said housing yet capable of moving said piston along said barrel thereby to express liquid out through said outlet.

Preferably the battery itself of said electrical circuit emits said gas or gases upon energisation of the electrical circuit by said battery.

5 In another form said electrical circuit defines an electrolysis cell with a hydrogel or electrolyte and the gas issues or gases issue from said hydrogel or electrolyte.

Preferably the battery powered electrical circuit includes a battery of a kind as disclosed in US Patent 5,242,565.

10 Preferably said battery powered electrical circuit, where an electrolysis cell is involved, includes an electrolysis cell of a kind as disclosed in US Patent 5,352,464.

Preferably said electrical circuit provides a continuous rate of gas production by the action of a continuous current to the electrolysis cell or gas emitting battery.

15 Alternatively said electrical circuit provides a discontinuous rate of gas production by the action of a discontinuous current, for example, as might be provided by a microprocessor, to the electrolysis cell or gas emitting battery.

Preferably where said battery powered electrical circuit provides a continuous rate of gas production, such production is dependent upon at least one of the group consisting of

- 20 (a) a selected resistor in series,
(b) a selected variable resistor and a setting of a desired resistance in series,
and
(c) a selected microprocessor to control the current.

25 Preferably the battery powered electrical circuit is one having a known or calibrated profile of gas generation that will lead to a related profile of liquid release from said outlet.

Preferably said device is an intra vaginal device .

Preferably said housing has associated therewith at least one deployable retention member to enable the retention of the device in the vagina after insertion in the vagina of a target mammal whilst said at least one retention member is not deployed.

30 Preferably said at least one retention member comprises at least two wings which resiliently deploy once inserted and preferably are no longer restrained by an insertion

tool.

Preferably the retention feature(s) is (are) those typified in the disclosure of PCT/NZ97/00052, PCT/NZ98/00011 and PCT/NZ98/00024 (and any specification referred to therein), the full content of which is hereby incorporated by way of
5 reference.

Preferably said liquid includes progesterone in an appropriate liquid carrier.

In another embodiment said device is an intra ruminal device.

Preferably said intra ruminal device is retainable in the rumen of a target mammal by means of its density (at least up until the depletion of the liquid from said
10 housing) or by deployment of at least one retention member.

Preferably said liquid includes at least one or more of water, ethanol and benzyl alcohol.

Preferably said battery powered electrical circuit includes a switch capable of being actuated immediately or after a delay to commence the generation of a gas or
15 gases.

Preferably said outlet is provided with a closure capable of being removed or ruptured or dissolved in body fluids.

Preferably said closure is capable of being removed or ruptured under the pressurisation of the liquid within said housing upon energisation of the battery powered
20 electrical circuit.

Preferably said liquid is of a volume of from 5 to 100 mL and said piston is movable within said housing to express substantially all of such liquid from the housing.

Preferably said device is insertable, retainable and removal from the vaginal tract of a target species mammal, there being a conduit or passageway disposed to allow
25 pressure equalisation outside of the device at the innermost and outmost extent of the device in the vaginal tract.

Preferably said device is substantially as hereinafter described with reference to the accompanying drawings.

In still another aspect the invention consists in an intra vaginal delivery device
30 comprising or including
a housing defining a barrel with an outlet,

0926745 03440

variable geometry vaginal retention means carried by said housing,
a piston disposed in said barrel and moveable to reduce the available volume for
liquid between said piston and said outlet,

a progesterone carrying liquid within said barrel between said outlet and said
5 piston, and

a battery powered electrical circuit disposed in said housing capable of being
energised to generate gas or gases from the battery of said battery powered electrical
circuit, such generated gas or gases being confined within said housing and being
capable of moving said piston along said barrel thereby to express liquid out through
10 said outlet

and wherein said battery powered electrical circuit provides a discontinuous or
continuous gas production upon initiation of energisation with rate and/or timing
dependent upon at least one of the group consisting of

- (a) a selected resistor in series,
- 15 (b) a selected variable resistor and a setting of a desired resistance in series,
and
- (c) a selected microprocessor to control the current.

In still a further aspect the present invention consists in an intra vaginal
delivery device comprising or including

20 an elongate housing defining a barrel with an outlet at one end (the "outlet end"),
a piston disposed in said barrel and moveable towards the outlet end to reduce
the available volume for liquid between said piston and said outlet,

a progesterone including liquid within said barrel between said outlet and said
piston, the volume of such liquid being from 5 to 100 mL,

25 wings dependent from said housing capable of self deployment from a vaginal
tract insertion condition to assume a vaginal tract retention geometry for the target
species mammal,

a battery powered electrical circuit disposed in said housing at the non outlet end
region thereof capable of being initialised in order to energise the electrical circuit from
30 the battery thereof, such battery generating once the electrical circuit is energised at
least one gas confined within said housing, such gas being capable when in sufficient

quantities to move said piston along said barrel thereby to express said liquid out through said outlet.

In another aspect the invention consists in a method of providing an active release of a liquid within a body cavity of a target species mammal which comprises
5 or includes locating in such a body cavity a device as claimed in any one of the preceding claims with said battery powered electrical circuit energised or committed to be energised.

In still another aspect the invention consists in a method of delivering an active amount of a progesterone into the vaginal tract of a target species mammal which
10 comprises

locating a device of the present invention in such tract after initiation of the device, and

allowing the device to actively express the liquid from said housing under the effect, via said piston, of the gas or gases generated by the energised battery powered
15 electrical circuit.

Preferably said method involves removing said device after a sufficient time of liquid delivery.

In another aspect the invention is a method when performed substantially as herein described with or without reference to any one or more of the accompanying
20 drawings.

In still other aspects the present invention consists in a method of providing a delayed release of a liquid vehicle into a body cavity of a mammal or into a liquid environment or other environment which comprises the operative use of a delivery device in accordance with the present invention.

Preferably said devices do not include a dip tube or the equivalent of a kind as defined in, for example, PCT/NZ98/00011.
25

In still a further aspect the present invention consists in an intra ruminal device which is also a delivery device in accordance with the present invention.

In still a further aspect the present invention consists in an intra vaginal device
30 which is also a delivery device in accordance with the present invention.

In still a further aspect the present invention consists in any of the devices or

apparatus previously defined whereby means is provided to enable for equalisation of pressures between the zone externally adjacent said outlet with some region of the device having a closer access to ambient condition when the device is retained in a body cavity, such means providing for fluid (preferably gas and preferably air) communication to minimise pressure differentials adjacent the outlet as a result of movement of walls of the body cavity and an air seal about the device in the body cavity.

Preferably the arrangement is of any kind typified by the diagrammatic form shown in, for example, Figure 5.

BRIEF DESCRIPTION OF THE DRAWINGS

Preferred forms of the present invention will now be described with reference to the accompanying drawings in which;

Figure 1A shows a balloon or membrane containing embodiment of a device,

Figure 1B is a piston including syringe-like embodiment,

Figure 2 is a plot for the Figure 1A and B embodiments of volume released against time,

Figure 3 compares for the Figures 1A device the *in vivo* and *in vitro* delivery profiles with a plot of volume release against time,

Figure 4 is a similar comparison for the Figure 1B device plotted in a similar fashion to that of Figure 3,

Figure 5 shows how (in this case for the more energy demanding but better *in vivo* delivery profile device - that of Figure 1B) the use of a tube whereby the transient pressure differentials (eg; in the vaginal tract) adjacent the outlet may be reduced,

Figure 6 is a plot of the plasma progesterone following intra vaginal insertion of a device of Figure 1A,

Figure 7 is a plot of the plasma progesterone following intra vaginal insertion of a device of Figure 1B with three different progesterone formulations,

Figures 8A through 8D show a simple circuit diagram each involving an electrolytic cell, Figure 8A shows an electrolytic cell in series with resistor and power source, Figure 8B shows an electrolytic cell in series with a variable resistor and power

source, Figure 8C shows an electrolytic cell controlled by powered microprocessor and Figure 8D shows an electrolytic cell controlled by powered microprocessor,

Figure 9A through 9D show a series of different circuits appropriate where a battery of a kind capable of generating a gas or gases is utilised in the circuit, Figure 9A showing a gas cell of the type described by US Patent 5,242,565 in series with a resistor, Figure 9B shows a gas cell of the type described by US Patent 5,242,565 in series with a variable resistor, Figure 9C shows a gas cell of the type described by US Patent 5,242,565 controlled by a gas cell of the type described by US Patent 5,242,565 powered microprocessor and Figure 9D shows a gas cell of the type described by US Patent 5,242,565 controlled by a microprocessor powered by an external power source, and

Figure 10A shows in broken outline two insertion conditions for self deployable wings and Figure 10B shows such wings deployed to a vaginal tract retention condition.

DETAILED DESCRIPTION OF THE INVENTION

The present invention recognises advantages that might flow to particularly body cavity retainable devices (eg; intra vaginal or intra ruminal devices) where a liquid vehicle is to be actively released and there is a desire to reduce the ratio of passive release to active release. In this respect embodiments to be discussed hereinafter recognise advantages that arise from the use of gas generation for the purposes of reducing the available volume in a reservoir for the liquid vehicle to be expressed.

For low energy usage preferably an inflatable device as hereinafter described by reference to Figure 1 is preferred yet surprisingly as will hereinafter be described we have determined that a plunger or piston like reservoir reduction provides a better *in vivo* release profile over that of the inflation option owing to a reduction in passive delivery. Where therefore rapid release with some passive content is not of concern significant energy savings are available for an active release device utilising the inflation option. Where however controlled release is of primary importance and/or there is no concern with an initial startup delay or a startup delay is desired the option hereinafter described by reference to Figure 1B with the use of a gas generated battery

is to be preferred even though it will be a higher energy requirement for such an option.

The devices of Figures 1A and 1B utilize electronically controlled gas to facilitate the delivery of a vehicle. The vehicle may be aqueous, organic or non-organic based. The production of gas may be from a suitable electrolytic material (US5352464) or galvanic cell (US 5242565) and is controlled by suitable circuitry.

The device of Figure 1A incorporates a balloon that upon the production of gas and its movement into the balloon means the balloon expands to fill the reservoir containing the liquid vehicle. This expansion results in the delivery of the liquid vehicle out of the outlet.

The device of Figure 1B incorporates a piston that upon the production of gas behind the piston results in its migration towards the outlet. This forward migration results in the delivery of the liquid vehicle.

In Figure 1A the balloon 1 is disposed within a syringe like reservoir 2 having an outlet 3. The liquid vehicle 4 is interposed between the walls of the reservoir 2 the outlet 3 and the balloon 1 so that inflation thereof will have the effect of expressing the liquid vehicle 4 out of the outlet 3. The inflation is by means of electronic gas production at 5 which feeds gas via an appropriate conduit 6 to the confines of the balloon or diaphragm 1. Such conduit is indicated as 6.

The arrangement as in Figure 1B is much the same save that instead of the balloon or membrane 1, a piston 7 is provided which will move to reduce the volume for the liquid vehicle 4 therebetween and the outlet 3.

In use when both devices of Figures 1A and 1B are operated with the same rate of gas production the arrangement as shown in Figure 1A with the inflatable balloon allows for a more rapid onset of delivery with a greater flow of vehicle compared to the piston arrangement which is characterised by a lag in the onset of delivery and a reduced delivery rate.

Accordingly for some applications the device of Figure 1 offers advantages over a device of Figure 1B. In the plot of Figure 2, the lag in the onset of delivery from the configuration of Figure 1B is readily apparent from the lower line on the graph,

Preferably the control circuitry involves a resistor (variable or otherwise) of an appropriate kind to affect the current flow. The circuitry may optionally be

microprocessor controlled.

The liquid vehicle is preferably at least primarily aqueous, organic or non-organic as far as its liquid content is concerned. Whilst in preferred forms the vehicle as a whole may be viewed overall as a liquid it need not necessarily be a solution. The liquid itself may be the active or merely a liquid carrier for the active elsewhere in the vehicle.

Accordingly, the term "liquid vehicle" or "liquid" should be interpreted as including any one or more of a suspension, a dispersion, an emulsion, a susproemulsion, a solution and the like, and preferably a progesterone including "liquid".

Whilst the arrangement of Figure 1A has definite efficiencies in respect of the energisation required for the purpose of gas generation per volume of liquid vehicle dispensed and the lack of delay in such dispensation, the device of a kind shown in Figure 1B has been found to improve the delivery of liquid vehicle whilst inserted into a body cavity such as the rumen or the vaginal cavity.

Figure 3 shows a plot of liquid vehicle delivered in grams against time and days with a device as depicted in Figure 1A. The straighter line is the *in vitro* delivery of vehicle from a device of Figure 1A whilst the more curved line represents the *in vivo* delivery profile for an identical device. It is therefore surprising that whilst a device as shown in Figure 1A has the comparative *in vitro/in vivo* profiles shown in Figure 3, that a device as shown in Figure 1B has more agreement between the *in vitro/in vivo* profiles. In this respect see Figure 4 where in a similar way to that of Figure 3 the comparative performance of a device as in Figure 1B is shown in the *in vitro* and *in vivo* delivery modes. That line indicated with the shaded squares represents the *in vivo* profile.

For the purpose of the generation of the data shown in Figures 3 and 4 the volume of liquid vehicle being dispensed was in each case water to be expressed out of a 2 mm diameter outlet. In each case the syringe like reservoir was of a cylindrical form and was powered over the duration of the comparative trials by a galvanic cell of the kind disclosed in US Patent 5242565 capable of generating over the life of the cell to depletion up to 180 ml of hydrogen when measured at normal atmospheric conditions at sea level.

Figure 5 shows a variation of the device as shown in Figure 1A. In this form means is provided to reduce variations at least over the medium term in the pressure differential in a body cavity with that of the ambient atmosphere. For this purpose a tube 8 is provided which, in the case of an intra vaginal device as shown in Figure 5 (the variable geometry wings not being shown for convenience, but do see our PCT/NZ97/00052 (published as WO97/40776)) tends to equilibralise pressure externally of the device in a vaginal tract. Indeed the tube 8 if flexible may serve in part as a withdrawal mechanism for the device and as a passageway 9 through to an outlet zone 10. Experimentation with, for example, cattle has shown in the short to medium terms significant fluctuations in the pressure about the outlet of devices of the kind shown in Figures 1A and 1B which have the effect of providing a different net force acting on the liquid vehicle yet to be expressed. This is particularly disadvantageous with the device of Figure 1A where there is (as demonstrated in Figure 2) a more rapid onset of delivery following any adjustment in pressure on the liquid vehicle.

Accordingly, the device of Figure 1B has a better profile under variations of vaginal tract pressure without any arrangement that seeks to reduce localised pressure variations externally of the device.

Description of the technology:

The devices depicted in Figures 1A and 1B utilize electronically controlled gas 5 to facilitate the delivery of a vehicle. The vehicle may be aqueous, organic or non-organic based. The production of gas may be from a suitable electrolytic material (US 5354264) or galvanic cell (US 5242565) and is controlled by suitable circuitry.

The top device of Figure 1A incorporates a balloon that upon the production of gas within 6 the balloon 1 expands to fill the reservoir 2 containing a vehicle 4. This expansion results in the delivery of the liquid vehicle out of the outlet 3.

The bottom device of Figure 1B incorporates a piston 7 that upon the production of gas behind 6 the piston results in its migration towards the outlet. This forward migration results in the delivery of vehicle.

Figure 3 shows both the in vitro and in vivo delivery of vehicle from a body cavity for the device of Figure 1A.

Figure 4 shows the in vitro and in vivo agreement of vehicle delivered for the device of Figure 1B.

The device of Figure 5 utilizes electronically controlled gas to facilitate the delivery of a vehicle. The vehicle may be aqueous, organic or non-organic based. The production of gas may be from a suitable electrolytic material (US 5354264) or galvanic cell (US 5242565) and is controlled by suitable circuitry.

The device of Figure 5 shows improvements to enable a more controlled delivery of vehicle to a body cavity. The addition of a tube 9 (or indeed any passageway from one end to the other) facilitates the maintenance of a constant pressure within the cavity 10 in relation to the exterior pressure 8.

Example 1:

Formulation: Progesterone 15 mg/ml dissolved in ethanol.

Device: As shown in Figure 1A

15 Comment: Delivery profile characterised by a dose dump soon after insertion, followed by a reduction in plasma progesterone delivery on day due to the dose dump. See Figure 6. Figure 6 shows a plot of plasma progesterone concentration following the intra vaginal insertion of a device as per Figure 1A. Error bars are standard error means.

20 Example 2:

Formulation 1: Progesterone 15 mg/ml dissolved in ethanol.

Formulation 2: Progesterone 15 mg/ml suspended in water.

Formulation 3: Progesterone 15 mg/ml dissolved in hydroxypropyl β -cyclodextrin (20%w/v) solution.

25 Device: As shown in Figure 1B.

Comment: Delivery profile characterised by a rapid rise to desired levels soon after insertion, followed by a controlled delivery of progesterone over the remained of the insertion period. See Figure 7. Figure 7 shows a plot of the plasma progesterone concentration following the intra vaginal insertion of a device as per Figure 1B containing 1 of 3 formulations; alcoholic solution (diamond symbol), aqueous

suspension (triangle symbol with broken line) or aqueous cyclodextrin (square symbol). Error bars are standard error means.

Figures 8A to 8D and Figures 9A to 9D describe options available for circuits
5 where respectively (Figures 8A to 8D) and electrolytic cell and (Figures 9A to 9D) a battery or gas cell of the type described by US Patent 5,242,565 is used. Appropriate electrolytic cell is that using, for example, a hydrogel as disclosed in US Patent 5,354,264.

The present invention as can be seen from the disclosure and the drawings
10 (including those of the prior art referenced earlier in respect of vaginal tract retention features) can be used to deliver progesterone requirements prior to active withdrawal to allow the onset of oestrus. Again reference is drawn to such art as to insertion, retention options and withdrawal facilitating options.

CLAIMS:

1. A liquid delivery device suitable for liquid delivery in a body cavity when inserted therein, said comprising or including
- 5 a housing defining a barrel with an outlet,
a piston disposed in said barrel and moveable to reduce the available volume for liquid between said piston and said outlet,
a liquid within said barrel between said outlet and said piston, and
a battery powered electrical circuit disposed in said housing capable of being energised to generate gas or gases confined within said housing yet capable of moving
- 10 said piston along said barrel thereby to express liquid out through said outlet.
2. A device as claimed in claim 1 wherein the battery itself of said electrical circuit emits said gas or gases upon energisation of the electrical circuit by said battery.
3. A device as claimed in claim 1 wherein said electrical circuit defines an electrolysis cell with a hydrogel or electrolyte and the gas issues or gases issue from
- 15 said hydrogel or electrolyte.
4. A device as claimed in claim 2 wherein the battery powered electrical circuit includes a battery of a kind as disclosed in US Patent 5,242,565.
5. A device as claimed in claim 3 wherein said battery powered electrical circuit includes an electrolysis cell of a kind as disclosed in US Patent 5,352,464.
- 20 6. A device of any one of the preceding claims wherein said electrical circuit provides a continuous rate of gas production by the action of a continuous current to the electrolysis cell or gas emitting battery.
7. A device of any one of claims 1 to 5 wherein said electrical circuit provides a discontinuous rate of gas production by the action of a discontinuous current, as
- 25 provided by a microprocessor, to the electrolysis cell or gas emitting battery.
8. A device of claim 6 wherein said battery powered electrical circuit provides a continuous rate of gas production dependent upon at least one of the group consisting of
- (a) a selected resistor in series,
- 30 (b) a selected variable resistor and a setting of a desired resistance in series,
and

(c) a selected microprocessor to control the current.

9. A device as claimed in claim 7 wherein said battery powered electrical circuit includes a selected microprocessor to control the current to the electrolysis cell or gas emitting cell.

5 10. A device as claimed in any one of the preceding claims wherein the battery powered electrical circuit is one having a known or calibrated profile of gas generation that will lead to a related profile of liquid release from said outlet.

11. A device as claimed in any one of the preceding claims which is an intra vaginal device.

10 12. A device as claimed in claim 11 wherein said housing has associated therewith at least one deployable retention member to enable the retention of the device in the vagina after insertion in the vagina of a target mammal whilst said at least one retention member is not deployable.

13. A device as claimed in claim 12 wherein said at least one retention member
15 comprises at least two wings which resiliently deploy once inserted.

14. A device as claimed in any one of the preceding claims wherein said liquid includes progesterone in an appropriate liquid carrier.

15. A device as claimed in any one of claims 1 to 10 which is an intra ruminal device.

20 16. A device as claimed in claim 15 wherein said intra ruminal device is retainable in the rumen of a target mammal by means of its density at least up until the depletion of the liquid from said housing or by deployment of at least one retention member.

17. A device as claimed in any one of the preceding claims wherein said liquid includes at least one or more of water, ethanol and benzyl alcohol.

25 18. A device as claimed in any one of the preceding claims wherein said battery powered electrical circuit includes a switch capable of being actuated to immediately or after a delay commence the generation of a gas or gases.

19. A device as claimed in any one of the preceding claims wherein said outlet is provided with a closure capable of being removed, ruptured or dissolved in body fluids.

30 20. A device as claimed in claim 19 wherein said closure is capable of being removed or ruptured under the pressurisation of the liquid within said housing upon

09926745-031102

energisation of the battery powered electrical circuit.

21. A device as claimed in any one of the preceding claims wherein said liquid is of a volume of from 5 to 100 mL and said piston is movable within said housing to express substantially all of such liquid from the housing.

5 22. A device of any one of the preceding claims insertable, retainable and removal from the vaginal tract of a target species mammal, there being a conduit or passageway disposed to allow pressure equalisation outside of the device at the innermost and outmost extent of the device in the vaginal tract.

23. A device as claimed in any one of the preceding claims substantially as
10 hereinbefore described with reference to the accompanying drawings.

24. An intra vaginal delivery device comprising or including
a housing defining a barrel with an outlet,
variable geometry vaginal retention means carried by said housing,
a piston disposed in said barrel and moveable to reduce the available volume for
15 liquid between said piston and said outlet,
a progesterone carrying liquid within said barrel between said outlet and said piston, and
a battery powered electrical circuit disposed in said housing capable of being energised to generate gas or gases from the battery of said battery powered electrical
20 circuit, such generated gas or gases being confined within said housing and being capable of moving said piston along said barrel thereby to express liquid out through said outlet

and wherein said battery powered electrical circuit provides a discontinuous or continuous gas production upon initiation of energisation with rate and/or timing
25 dependent upon at least one of the group consisting of

- (a) a selected resistor in series,
- (b) a selected variable resistor and a setting of a desired resistance in series,
and
- (c) a selected microprocessor to control the current.

30 25. An intra vaginal delivery device for a target species mammal comprising or including

an elongate housing defining a barrel with an outlet at one end (the "outlet end")
a piston disposed in said barrel and moveable towards the outlet end to reduce
the available volume for liquid between said piston and said outlet,

a progesterone including liquid within said barrel between said outlet and said
5 piston, the volume of such liquid being from 5 to 100 mL,

wings dependent from said housing capable of self deployment from a vaginal
tract insertion condition to assume a vaginal tract retention geometry for the target
species mammal,

a battery powered electrical circuit disposed in said housing at the non outlet end
10 region thereof capable of being initialised in order to energise the electrical circuit from
the battery thereof, such battery generating once the electrical circuit is energised at
least one gas confined within said housing, such gas being capable when in sufficient
quantities to move said piston along said barrel thereby to express said liquid out
through said outlet.

15 26. A method of providing an active release of a liquid within a body cavity of
a target species mammal which comprises or includes

locating in such a body cavity a device as claimed in any one of the preceding
claims with said battery powered electrical circuit energised or committed to be
energised.

20 27. A method of delivering an active amount of a progesterone into the vaginal
tract of a target species mammal which comprises or includes

locating a device as claimed in any one of claims 1 to 25 in such tract after
initiation of the device, and

allowing the device to actively express the liquid from said housing under the
25 effect, via said piston, of the gas or gases generated by the energised battery powered
electrical circuit.



28. A method as claimed in claim 27 wherein said method involves removing said
device after a sufficient time of liquid delivery.

29. A method of providing delayed release of a liquid vehicle into a body cavity of
30 a mammal or into a liquid environment which comprises or includes the operative use
of a device of any one of claims 1 to 25.


30. A method as claimed in any one of claims 26 to 29 when performed substantially as hereinbefore described with or without reference to any one or more of the accompanying drawings.

0906745 0340
"00760" 54/92560

1/9

**FIGURE 1A****FIGURE 1B**

2/9

**FIGURE 2**

3/9




FIGURE 3

4/9






FIGURE 4

5/9

**FIGURE 5****FIGURE 6**

6/9


**FIGURE 7**

FIGURE 8A




FIGURE 8B




FIGURE 8C









FIGURE 8D



001016745

8/9

FIGURE 9A**FIGURE 9B****FIGURE 9C****FIGURE 9D**




FIGURE 10A




FIGURE 10B

2017E0" 54292660

DECLARATION AND POWER OF ATTORNEY U.S.A.

FOR ATTORNEYS' USE ONLY
ATTORNEYS' DOCKET NO.

ALL PATENTS, INCLUDING DESIGN
FOR APPLICATION BASED ON PCT; PARIS CONVENTION;
NON PRIORITY; OR PROVISIONAL APPLICATIONS

As a below named inventor, I declare that my residence, post office address and citizenship are stated below next to my name, the information given herein is true, that I believe that I am the original, first and sole inventor (if only one name is listed at 201 below), or an original, first and joint inventor (if plural inventors are named below at 201-203, or on additional sheets attached hereto) of the subject matter which is claimed and for which patent is sought on the invention entitled:

Device for Delivery of a Liquid Vehicle

which is described and claimed in: ☒ PCT International Application No. PCT/NZ00/00093 filed 11/06/1999
the attached specification the specification in application Serial No. 336241 filed 11/06/1999
(if applicable) and amended on 11/06/1999

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56. I hereby claim foreign priority benefits under Title 35, United States Code, §119 (a)-(d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)	(Number)	(Country)	(Day/Month/Year Filed)	Priority Claimed
336241	New Zealand	11/06/1999	X	
			Yes No	
			Yes No	
			Yes No	

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States provisional application(s) listed below:

Application No.	Filing Date	Application No.	Filing Date

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing Date)	(Status: patented, pending, abandoned)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorneys (Registration No.) to prosecute this application, receive and act on instructions from my agent, and transact all business in the Patent and Trademark Office connected therewith. HARVEY B. JACOBSON, JR. (20,851); JOHN CLARKE HOLMAN (22,769); MARVIN R. STERN (20,640); ALLEN S. MELSER (27,215); MICHAEL R. SLOBASKY (26,421); JONATHAN L. SCHERER (29,851); IRWIN M. AISENBERG (19,007); WILLIAM E. PLAYER (31,409); YOON S. HAM (45,307) and NATHANIEL A. HUMPHRIES (22,772)

SEND CORRESPONDENCE TO: CUSTOMER NO. 00138
or

JACOBSON HOLMAN,
PROFESSIONAL LIMITED LIABILITY COMPANY
400 SEVENTH STREET, N.W.
WASHINGTON, D.C. 20004

DIRECT TELEPHONE CALLS TO:
(please use Attorney's Docket No.)
(202) 638-6666

JACOBSON HOLMAN,
PROFESSIONAL LIMITED LIABILITY
COMPANY

*Inventor(s) name must include at least one unabbreviated first or middle name.

	FULL NAME * OF INVENTOR	FAMILY NAME	GIVEN NAME	MIDDLE NAME
1-00	BUNT	CRAIG	Robert	
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	HAMILTON NZX	Hamilton	NEW ZEALAND	New Zealand
20	POST OFFICE ADDRESS	CITY	STATE OR COUNTRY ZIP CODE	
	11 Queens Road	Hamilton	New Zealand	
2-00	RATHBONE	Michael	John	
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	HAMILTON NZX	Hamilton	NEW ZEALAND	British
20	POST OFFICE ADDRESS	CITY	STATE OR COUNTRY ZIP CODE	
	11 Walsh Street	Hamilton	New Zealand	
3-00	BURGGRAAF	Shane		
	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	HAMILTON NZX	Hamilton	NEW ZEALAND	British
20	POST OFFICE ADDRESS	CITY	STATE OR COUNTRY ZIP CODE	
	25 Richmond Road	Hamilton	New Zealand	

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both, under section 1001 of Title 18 of the United States Code; and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

SIGNATURE OF INVENTOR 201*	SIGNATURE OF INVENTOR 202*	SIGNATURE OF INVENTOR 203*
DATE	DATE	DATE
Additional inventors are named on separately numbered sheets attached hereto.		

* JH 2001 (COPYING WITHOUT DELETIONS PERMITTED)

093430 "544350